# MV Kalamazoo

| | |
|---|---|
| **Ship Name:** | Kalamazoo |
| Built: | 2013 Taizhou Kouan Shipbuilding Co. Ltd., China |
| Type: | 1100 TEU Cellular Container Vessel, Gearless |
| Class: | GL +100 A5 E, Container Ship, IW, NAV-O, BWM, DG, EP, +MC E AUT |
| | |
| International Tonnage: | 9,743 GT / 4,679 NT |
| Length overall: | 143.2 m |
| Beam moulded: | 22.6 m |
| Depth to main deck: | 11.3 m |
| Design draft: | 6.7 m with deadweight 8,411 mt |
| Scantling draft: | 8.3 m with deadweight 12,580 mt |
| Lightship: | 4,828 mt |
| Flag: | Singapore |
| P&I Club: | The Swedish Club |

**Container capacity**

Cell guides in holds for 20'/40' containers; on deck with lashing fittings for 20'/40'/45' containers. All containers intakes are always subjected to vessel's stability, trim, deadweight, permissible weights, permissible lashing gear break loads, container lashing plan, ranges of visibility, Panama Canalregulations and OSHA rules in which case intakes and stack weights can be considerably reduced. Distribution of container weights within a single stack (20' or 40') on deck shall comply with on boardcontainers stowage and lashing manual approved by class.

Homogeneous intake basis 14 mts about 649 TEU
40' high cubes in holds about 86 FEU (top two tiers available for 9'6" high cubes)
40' high cubes on deck about 174 FEU (subjected to IMO navigation visibility requirement)Maximum reefer containers loadable about 119 units at (7kW x 0.6 per unit)

| Stack weight | 20' TEU | 40' FEU |
|---|---|---|
| On Hatch/deck: | 60 mt | 90 mt |
| In Hold | 100 mt | 130 mt |

| | Tier | Max. 20' | Alternative 40' | Alternative 45' | Reefer Plugs |
|---|---|---|---|---|---|
| On Hatch | 92 | 54 | 27 | 0 | 0 |
| | 90 | 108 | 54 | 9 | 0 |
| | 88 | 140 | 70 | 27 | 0 |
| | 86 | 140 | 70 | 27 | 0 |
| | 84 | 140 | 70 | 27 | 0 |
| | 82 | 140 | 70 | 0 | 35 |
| On Deck | 80 | 4 | 2 | 0 | 42 |
| | Sum | 726 | 363 | 90 | 77 |

All Details are About. Given in good faith but without guarantee.

# MV Kalamazoo

| | | | | | |
|---|---|---|---|---|---|
| In Hold | 08 | 92 | 45 | 0 | 17 |
| | 06 | 86 | 41 | 0 | 17 |
| | 04 | 78 | 37 | 0 | 17 |
| | 02 | 60 | 28 | 0 | 17 |
| | Sum | 316 | 151 | 0 | 68 |
| | Total | 1042 | 514 | 90 | 145 |

IMDG cargoes

In No.1 hold : 1.4S, 2.1, 2.2, 2.3, 3.1, 3.2, 4.1, 4.2, 4.3, 5.1, 6.1, 8 & 9.

On hatches : 1(1.1 to 1.6 & 1.4S), 2.1, 2.2, 2.3, 3.1, 3.2, 4.1, 4.2, 4.3, 5.1, 5.2, 6.1, 8 & 9.

**Cargo holds and hatch covers**

Total 4 holds with open type pontoon hatch covers. No.1 cargo hold is single hold with one hatch cover. No.2 to No.4 cargo holds each divided into two compartments, each compartment has two split type hatch covers, the split is in way of Row 02 (Port side), can be opened in unconstrained sequence.

**Hatch covers size and weight**

No.1 about 13220x12740mm, 29mt

No. 2A/2B/3A/3B/4A/4B (Port side) each about 12740x7894mm, 21mt

No. 2A/2B/3A/3B/4A/4B (Stbd side) each about 12740x10417mm, 26mt

**Cargo holds ventilation**

Cargo hold No.1 natural supply and electrical driven flame proof exhaust fans.

Cargo hold No.2 to No.4 electrical driven exhaust & supply fans.

Cargo holds are fitted with CO2 fire extinguishing system.

| | | | |
|---|---|---|---|
| Tank capacity: | Ballast about 5,021 cu.m | VLSFO | about 830 cu.m |
| FW | about 200 cu.m | MDO | about 120 cu.m |

Endurance about 10,000 nm

Main engine 1x QMD Wartsila 6RT-Flex48T-D with MCR 8730 kW at 127 rpm.

Electric generator 3 x 730 kW each driven by Anqing Diahatsu 5DK-20e 800kW at 900 rpm

**Sea speed and consumption:**

At 17 knots under trial condition on design draft of 6.7m, with clean bottom, even keel, deep sea water, no wind, no wave, no current, the fuel consumption is about 20 mt/day (+ 5% tolerance).

Aux engine consumption is about 3 mt per engine per day excluding heating and reefer containers.

Following speed/consumption for reference purpose only:

All Details are About. Given in good faith but without guarantee.

# MV Kalamazoo

| Design draft 6.7 m | Scantling draft 8.3 m |
|---|---|
| 12.0 kn about 9.0 mt per day | 12.0 kn about 10.0 mt per day |
| 13.0 kn about 10.0 mt per day | 13.0 kn about 11.5 mt per day |
| 14.0 kn about 12.0 mt per day | 14.0 kn about 13.5 mt per day |
| 15.0 kn about 14.0 mt per day | 15.0 kn about 16.0 mt per day |
| 16.0 kn about 17.0 mt per day | 16.0 kn about 20.0 mt per day |
| 16.5 kn about 18.5 mt per day | 16.5 kn about 22.0 mt per day |
| 17.0 kn about 20.0 mt per day | 17.0 kn about 24.0 mt per day |

Main Engine power to attain required EEXI is 6995kW and EEXI reference speed (EPL) is indicated to be 17.25Kn. Overriding the limitation is a safety feature which may only be used under certain conditions as stipulated in the EPL guideline issued by the IMO. Special requirements related to documentation prevails in such circumstances.
In line with maker's technical advice, to inter alia avoid premature cold corrosion and wastage of diesel engine exhaust valves, the diesel engines must burn MGO rather than VLSFO when running on engine operating load less than 25 % of MCR.

Furthermore, when the vessel is transiting narrow and/or shallow waters and/or waters traversed by bridges and/or waters near or between islands or through congested waters then for safety reasons (as reasonably determined by the Master) and as per company procedures, the vessel must run two diesel generators at a low engine operating load of less than 25% of MCR. As per above paragraph, when diesel engine operating load is less than 25% then the vessel will be required to change over from, VLSFO to MGO.

All above figures are based on ISO reference conditions and fuel oil with minimum calorific value of 42700 kJ/kg. Vessel can operate on single fuel system using marine fuel oil; sufficient quantity of marine diesel shall be provided for emergency operation. Fuel oil specification shall comply with ISO 8217:2010 or any subsequent amendment, the marine fuel oil shall equal to RMG or better, and the marine diesel oil shall equal to DMB or better. Charterers shall only supply suitable fuels to enable
main propulsion and auxiliary machinery to operate efficiently and without harmful effects. Fuels to be mineral based products, stable and homogeneous and shall not contain waste lubricants, chemicals or any other harmful substances; sludge removal, if any, to be always for Charterers' account and time. Supplied fuels shall comply with the requirement imposed by IMO and respective region/country.

**Fittings:**
Fittings for Suez/Panama canals, bow thruster about 590kW, satellite communication
(telex/phone/fax/email)

**Miscellaneous:**
Owner: Eday Shipping Pte. Ltd.
Technical Manager: Norse Ship Management Pte. Ltd. (Singapore)

All Details are About. Given in good faith but without guarantee.